FTP-1514 Series for 40 Gbps Links Completely passive fault tolerant design. Link access, anytime.

Ideal for permanent, 24x7 access to your fiber network for Network Analysis, IDS and monitoring applications

40 Gigabit fiber taps from Datacom Systems provide your network monitoring and security tools passive permanent access into your 40 Gigabit fiber network.

These network taps are ideal for security applications, network monitoring and anywhere you need to see all the data that only an In-Line solution can provide. Invisible to the network, completely passive and fault-tolerant, fiber taps will not affect network performance or integrity.



They provide permanent In-Line access to network links eliminating the need for network connectors to be disconnected and connected each time a segment needs to be analyzed.

Our taps allow you to view layer 1 and 2 errors not seen when performing network monitoring using SPAN ports.

No Y or breakout cable required Optional 1U rack mount holds 3 taps 4U 12 bay rack available

Find out more. Visit www.datacomsystems.com

Technical Specifications

NETWORK PORT

Two (2) 40Gb MTP Network Connections MONITOR PORT

Two (2) 40Gb MTP Monitor Connections

SPLIT RATIO

50/50, 70/30

INSERTION LOSS*

50/50 split ratio results in a 4.6 dB insertion loss 70/30 split ratio results in a 6.6/2.6 dB insertion loss * approximate per fiber

PHYSICAL DIMENSIONS (H x W x D)

1.07 x 5 x 7 (2.7 x 12.7 x 17.78 kgs)

WEIGHT

15 oz (0.43 kgs)

CERTIFICATIONS

CE, ROHS

ENVIRONMENTAL

Operating Temperature: 32° to 104°F (0° to 40°C) Storage Temperature: -22° to 149°F (-30° to 65°C) Humidity: 5 to 90% non-condensing

WARRANTY

Two (2) Year Standard Hardware Warranty

ORDERING INFORMATION

Product FTP-1514

FTP-1714

Optional Equipment RMC-3

RMC-12-3

Description

40Gb Passive TAP with 2 MTP ports, to tap a 12 fiber strand link. 50/50 split ratio. 50 micron fiber, with 2 separate MTP output ports 40Gb Passive TAP with 2 MTP ports, to tap a 12 fiber strand link. 70/30 split ratio. 50 micron fiber, with 2 separate MTP output ports

3-Unit Rack Mount 12-Unit Rack Mount

